

# TIMBER BRIDGE

# W0070

Central point for tree surging harness Timber II.

CE 1019



singing rock

SAFETY  
FIRST



SIZE: UNI

Directive / směrnice  
PSA 89/686/EEC  
Nař. vlády 21/2003 Sb.

Certified by / certifikoval  
VVUÚ, a.s. Ostrava-Radvanice  
Pikartská 1337/7, ČR

EC QMS of production inspected by /  
ES SRJ výroby prověřuje  
VVUÚ, a.s. Ostrava-Radvanice  
Pikartská 1337/7, ČR



3 years guarantee  
3 roky záruka



Reading and understanding instruction  
for use are required to use this product!  
Bez důkladného přečtení a pochopení návodu  
k použití nepoužívejte tento výrobek

## Description and technical information

- Replacement connecting loop through the schackle is intended to exchange worn-out connecting loop on the harness Timber II.
- Loop connecting the central components of the locking points at the harness Timber II.
- Bright red color makes it able to move freely in the trees
- Material composition: PAD, strap width-20 mm, length of Timber Bridge-32.5 cm, weight - 37 g.

## The exchange of the central point:

1. To disassemble the central point use an allen key # 4 to unscrew two shackles.
  2. Insert the new central point in one of the shackles; ensure that the shackle is free of any burrs and grease, screw and tighten with the force of 5 Nm.  
Note: For each exchange of the central point we recommend to use Loctite® glue on the screw.
  3. Repeat the above operations for the other side.
- Beware of the correct connection of the shackles!  
Screw head must be directed upwards.

