

Fully adjustable harness for rope access with a padded wide waist belt, leg loops and shoulder straps. Suitable for work positioning, fall arrest and work restraint situations. This harness is specially intended for workers at offshore oil platforms.

DESCRIPTION

Webbings stitched in the easylock buckles on the shoulder straps simplify handling. A different strap color is used for different harness sizes.

Front attachment point marked with the letter A, stainless "D" point with a load capacity of 15 kN.

3 braided gear loops with a bearing capacity of 5 kg.

Combination of standard and COBRA speed buckles enable fluent and fast adjustment to fit the users body.



Stainless steel buckles.

Easy fixing of CAM CLEAN ascender in vertical position is provided by stitched strap.

Wide waist belt provides maximum comfort when working at height.

Side attachment points for work positioning according to EN 358 using connectors EN 362.

KEY FEATURES

stainless steel components makes the harness ultimate choice for offshore operations

STANDARDS

C€ 1019

EN 361:02 EN 813:08 EN 358:18

FEATURES



warranty



1650 g S / 58.202 oz 1750 g M/L / 61.729 oz Czech Republic 1910 g XL / 67.373 oz



Made in

MATERIALS



- 38% PAD
- 25 % stainless steel
- 17 % aluminium alloy
- 13 % EVA foam
- **7%** PES

SIZE CHART







_	_
В	


		S	M/L	XL
С	A [cm/in]	65-80 / 25-31	75–100 / 29–39	85-130 / 33-51
	B [cm/in]	45-60 / 18-24	50-75 / 19-29	50-75 / 19-29
	C [cm/in]	150-170 / 59-67	160-180 / 63-70	175-205 / 68-80
	m [g]	1 650 g	1750 g	1 910 g




W0074 Version: 02/2021


TECHNICAL DATA

COBRA



DOUBLE






A EN 361:02
B EN 813:08

© EN 358:18

MRL = 150 kg



MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use. However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



beware of salt



beware of UV



beware of chemicals



washing



drying



read instructions

RELATED PRODUCTS



ROOF MASTER

W0091BY



TACTIC MASTER

W0096BB

STANDARDS	EN 358; EN 361; EN 813	EN 358; EN 361; EN 813
WEIGHT	1570 g (size M/L)	1740 g (size M/L)

NOTES

