

# ↑ EvaQ HUB

Descender and rescue device with lifting function for height rescue by fire fighters, industrial climbers and others when exposed to a danger at great heights such as cable cars, outdoor parks, wind power plants or scyscrapers. Also suitable for quick and easy rescue and even for self-rescue of many threatened people.

## DESCRIPTION

Closed handwheel made of durable plastic for easy and save operation even in hard condition and under full load.

Designed for working load 225 kg (2 persons).

Three stainless steel eyebolts for smooth descend speed control and multiple operation modes. Back side rope clamp for easy lifting operation.

Static polyamide kernmantle rope acc. to EN 1891-A,  $\varnothing$  9.6 mm. Both ends are equipped with stitched eye and steel double trigger automatic locking connector with gate opening of 21mm.



Steel double trigger automatic locking connector with gate opening of 21 mm for versatile and easy hanging.

Hexagon connector for battery screw driver as standard.

Automatic and redundant brake system with 2 fly wheel brakes. Brake drums are made from steel for high resistance.

### KEY FEATURES

- Max. working load: 225 kg
- Max. descend/lifting height: 300 m
- Descend speed: ca. 0.8 m/s
- Operable temperature: -40 °C to +65 °C

## STANDARDS



EN 1496:2007-B  
EN 341:2011-1A

## FEATURES



225 kg



max  
300 m



3.4 kg / 121 oz  
(+ rope)



unique  
number



2  
YEARS  
warranty

## TECHNICAL DATA



