



Durable lanyard made of 23 mm webbing with stitched eyes and wear indicator for positioning not only in rope parks.

DESCRIPTION

Can be used as an anchoring or connecting device for work at height.

Webbing is constructed of two parts with a strength core inserted into a hollow protective cover.

For use in accordance with EN17109, a connection device according to EN 17109 must also be used.

For use in accordance with EN354, the maximum permissible length in the fall arrest system is 2 m.



It must not be used alone as a fall arrest device.

In case that the outer webbing is damaged, the user will be immediately alerted by the glowing colour of the inner webbing to the danger of further use.

Attachment to the harness via larks foot or suitable connection device (f.e. RINGO, maillon).

KEY FEATURES

- wear indicator
- certified according to EN17109

STANDARDS

CE 1019

EN 795B EN 566

EN 354 EN 17109

FEATURES



strength
22 kN



1 person
only




unique
number



3
years
warranty

MATERIALS



- 99% PAD
- 1% PES

TECHNICAL DATA

	CODE	LENGTH*	WEIGHT
TENDRIL "I"	W2530B070	70 cm	80 g
TENDRIL "I"	W2530B095	95 cm	100 g
TENDRIL "V"	W2550B070	70/70 cm	120 g
TENDRIL "V"	W2550B095	95/95 cm	160 g

*Other lengths according to customer's request.

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use. However mechanical damage can occur during the first use, which can limit the lifetime of this products only to its first use.



beware of
salt



beware of
UV



beware of
chemicals



washing



drying



read
instructions

RELATED PRODUCTS

	 <p>LANYARD "I" W2300*</p>	 <p>LANYARD "V" W2200*</p>	 <p>SLING LANYARD W2016*</p>
STRENGTH	22 kN	22 kN	22 kN
LENGTH	60–150 cm 24–60 in	25/45 cm; 25/65 cm; 100/100 cm 10/17 in; 10/30 in; 40/40 in	60–150 cm 24–60 in

NOTE: This area contains a grid of plus signs (+) for additional notes.