
































DYNAMIC ROPES		CODE	COLOR	LENGTH m	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	DYNAMIC ELON- GATION %	NUMBER OF FALLS	IMPACT FORCE kN	TYPE	STANDARD	€€
GEMINI 79 DRY 	Half & twin rope for mountaineering, ice climbing or glacier tours with special water repellent treatment.	L3020YX03	yellow	30 m	7.9	39	8 (twin); 10.5 (half)	33 (twin); 38 (half)	16 (twin); 5 (half)	7.9 (twin); 5.1 (half)	half-twin	EN 892 A Ω	€€ 1019
		L3020YX04		40 m									
		L3020YX05		50 m									
		L3020YX06		60 m									
		L3020YX07		70 m									
		L3020YX08		80 m									
		L3020YX10		100 m									
		L3021YX20		200 m spool									
		L3020RX03	red	30 m									
		L3020RX04		40 m									
		L3020RX05		50 m									
		L3020RX06		60 m									
		L3020RX07		70 m									
		L3020RX08		80 m									
		L3020RX10		100 m									
		L3021RX20		200 m spool									
ACCORD 8.3 DRY 	Half and twin rope with excellent durability and special water repellent treatment.	L0514OG03	orange	30 m	8.3	43	6.4 (twin); 11 (half)	34 (twin); 33 (half)	15 (twin); 5 (half)	9.7 (twin); 6.3 (half)	half-twin	EN 892 A Ω	€€ 1019
		L0514OG04		40 m									
		L0514OG05		50 m									
		L0514OG06		60 m									
		L0514OG07		70 m									
		L0514OG08		80 m									
		L0514OG10		100 m									
		L0515GO20		200 m spool									
		L0514GO03	green	30 m									
		L0514GO04		40 m									
		L0514GO05		50 m									
		L0514GO06		60 m									
		L0514GO07		70 m									
		L0514GO08		80 m									
		L0514GO10		100 m									
		L0515GO20		200 m spool									
ACCORD 8.3 	Durable half & twin rope for trad climbing.	L0510GA03	green	30 m	8.3	43	6.4 (twin); 11 (half)	34 (twin); 33 (half)	15 (twin); 5 (half)	9.7 (twin); 6.3 (half)	half-twin	EN 892 A Ω	€€ 1019
		L0510GA04		40 m									
		L0510GA05		50 m									
		L0510GA06		60 m									
		L0510GA07		70 m									
		L0510GA08		80 m									
		L0510GA10		100 m									
		L0511GA20		200 m spool									
		L0510AG03	blue	30 m									
		L0510AG04		40 m									
		L0510AG05		50 m									
		L0510AG06		60 m									
		L0510AG07		70 m									
		L0510AG08		80 m									
		L0510AG10		100 m									
		L0511AG20		200 m spool									
DNA 8.9 DRY 	One rope for all your climbing activities. Suitable for sport climbing and also for mountaineering and glacier tours thanks to its lightness and water resistance.	L3060CX03	pink	30m	8.9	56	32 (single) 27 (half) 25 (twin)	4 (single) 4 (half) 3 (twin)	5 (single) 15 (half) 30 (twin)	9 (single) 7.2 (half) 11 (twin)	single, twin and half	EN 892 A Ω	€€ 1019
		L3060CX04		40m									
		L3060CX05		50m									
		L3060CX06		60m									
		L3060CX07		70m									
		L3060CX08		80m									
		L3060CX10		100m									
		L3061CX20		200 m spool									





DYNAMIC ROPES		CODE	COLOR	LENGTH m	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	DYNAMIC ELON- GATION %	NUMBER OF FALLS	IMPACT FORCE kN	TYPE	STANDARD	CE
 <p>ICON 9.3 DRY</p>	<p>Lightweight and water resistant single rope made with patented R44 technology for your sport climbing projects.</p>	L0384RX03	red	30 m	9.3	57	9	32	5	8.6	single	EN 892 	CE 1019
		L0384RX04		40 m									
		L0384RX05		50 m									
		L0384RX06		60 m									
		L0384RX07		70 m									
		L0384RX08		80 m									
		L0384RX10		100 m									
		L0385RX20		200 m spool									
 <p>ICON 9.3</p>	<p>Lightweight single rope made with patented R44 technology for your sport climbing projects.</p>	L0380YX03	yellow	30 m	9.3	57	9	32	5	8.6	single	EN 892 	CE 1019
		L0380YX04		40 m									
		L0380YX05		50 m									
		L0380YX06		60 m									
		L0380YX07		70 m									
		L0380YX08		80 m									
		L0380YX10		100 m									
		L0381YX20		200 m spool									
 <p>HERO 9.6 DRY</p>	<p>Top-class water resistant single rope with low weight for high-level climbers.</p>	L0524GW03	blue	30 m	9.6	59	5.1	35	8	7.9	single	EN 892 	CE 1019
		L0524GW04		40 m									
		L0524GW05		50 m									
		L0524GW06		60 m									
		L0524GW07		70 m									
		L0524GW08		80 m									
		L0524GW10		100 m									
		L0525GW20		200 m spool									
 <p>HERO 9.6</p>	<p>Single rope with great handling for sport climbers.</p>	L0520GA03	green	30 m	9.6	59	5.1	35	8	7.9	single	EN 892 	CE 1019
		L0520GA04		40 m									
		L0520GA05		50 m									
		L0520GA06		60 m									
		L0520GA07		70 m									
		L0520GA08		80 m									
		L0520GA10		100 m									
		L0521GA20		200 m spool									
 <p>KATA 9.7 DRY</p>	<p>High-end water resistant single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.</p>	L0580AA03	blue	30 m	9.7	61	9	30	5	7.7	single	EN 892 	CE 1019
		L0580AA04		40 m									
		L0580AA05		50 m									
		L0580AA06		60 m									
		L0580AA07		70 m									
		L0580AA08		80 m									
		L0580AA10		100 m									
		L0581AA20		200 m spool									
 <p>KATA 9.7</p>	<p>High-end climbing single rope with high safety factors and extremely high durability. Suitable for both experienced climbers and beginners.</p>	L0570AA03	light blue	30 m	9.7	61	9	30	5	7.7	single	EN 892 	CE 1019
		L0570AA04		40 m									
		L0570AA05		50 m									
		L0570AA06		60 m									
		L0570AA07		70 m									
		L0570AA08		80 m									
		L0570AA10		100 m									
		L0571AA20		200 m spool									
 <p>STORM 9.8 DRY</p>	<p>Water resistant single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.</p>	L3044AG03	blue	30m	9.8	65	7.9	35	9	9.1	single	EN 892 	CE 1019
		L3044AG04		40m									
		L3044AG05		50m									
		L3044AG06		60m									
		L3044AG07		70m									
		L3044AG08		80m									
		L3044AG10		100m									
		L3045AG20		200 m spool									




DYNAMIC ROPES		CODE	COLOR	LENGTH m	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	DYNAMIC ELON- GATION %	NUMBER OF FALLS	IMPACT FORCE kN	TYPE	STANDARD	€€
STORM 9.8 	Single rope with great balance in weight, durability and use. Perfect choice for all-round climbing.	L3040GA03	green	30 m	9.8	65	7.9	35	9	9.1	single	EN 892 △ M	€€ 1019
		L3040GA04		40 m									
		L3040GA05		50 m									
		L3040GA06		60 m									
		L3040GA07		70 m									
		L3040GA08		80 m									
		L3040GA10		100 m									
		L304IGA20		200 m spool									
GYM 9.8 	Single rope specially designed for the demanding conditions of rentals of climbing walls or rope centres and parks.	L3070YX03	yellow	30 m	9.8	63	8	33	8	9.1	single	EN 892 △ M	€€ 1019
		L3070YX04		40 m									
		L3070YX05		50 m									
		L3070YX06		60 m									
		L3070YX07		70 m									
		L3070YX08		80 m									
		L3070YX10		100 m									
		L3070YX20		200 m spool									
GYM 10.1 	Single rope specially invented for climbing gyms, adventure parks or rope courses.	L3050RY03	red	30 m	10.1	67.8	7.4	37	7	7.9	single	EN 892 △ M	€€ 1019
		L3050RY04		40 m									
		L3050RY05		50 m									
		L3050RY06		60 m									
		L3050RY07		70 m									
		L3050RY08		80 m									
		L3050RY10		100 m									
		L305IRY20		200 m spool									
SCORE 10.1 DRY 	Water resistant single rope for the gym or crags.	L0364LA03	mint	30 m	10.1	66	7	32	8	9.5	single	EN 892 △ M	€€ 1019
		L0364LA04		40 m									
		L0364LA05		50 m									
		L0364LA06		60 m									
		L0364LA07		70 m									
		L0364LA08		80 m									
		L0364LA10		100 m									
		L0365LA20		200 m spool									
SCORE 10.1 	Great single rope for the gym or crags with shiny colour.	L0360GG03	green	30 m	10.1	66	7	32	8	9.5	single	EN 892 △ M	€€ 1019
		L0360GG04		40 m									
		L0360GG05		50 m									
		L0360GG06		60 m									
		L0360GG07		70 m									
		L0360GG08		80 m									
		L0360GG10		100 m									
		L036IGG20		200 m spool									
DURAN 10.4 	Durable rope for rope courses and gym climbing.	L0340AX03	blue	30 m	10.4	68	7.1	31	8	9.8	single	EN 892 △ M	€€ 1019
		L0340AX04		40 m									
		L0340AX05		50 m									
		L0340AX06		60 m									
		L0340AX07		70 m									
		L0340AX08		80 m									
		L0340AX10		100 m									
		L034IAX20		200 m spool									



DYNAMIC ROPES		CODE	COLOR	LENGTH m	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	DYNAMIC ELON- GATION %	NUMBER OF FALLS	IMPACT FORCE kN	TYPE	STANDARD	CE
PATRON 11.0 	Dynamic single rope with high safety factor and great durability.	L0540BB03	black	30 m	11	79	5.3	31	16	9.1	single	EN 892 Ⓢ	CE1019
		L0540BB04		40 m									
		L0540BB05		50 m									
		L0540BB06		60 m									
		L0540BB07		70 m									
		L0540BB08		80 m									
		L0540BB10		100 m									
		L0541BB20		200 m spool									
		L0540YX03	yellow	30 m									
		L0540YX04		40 m									
		L0540YX05		50 m									
		L0540YX06		60 m									
		L0540YX07		70 m									
		L0540YX08		80 m									
		L0540YX10		100 m									
		L0541YX20		200 m spool									


LOW STRETCH ROPES		CODE	COLOR	LENGTH m	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC R44 11.0 	Excellent quality STA-TIC rope intended for rope access, work positioning, rescue or manipulation with the objects.	L0450BB03	black	30 m	11	77	3.2	34.9	22.3	20	A	EN 1891 Ⓢ	CE1019
		L0450BB04		40 m									
		L0450BB05		50 m									
		L0450BB06		60 m									
		L0450BB07		70 m									
		L0450BB08		80 m									
		L0450BB10		100 m									
		L0451BB10		100 m spool									
		L0451BB20	orange	200 m spool									
		L0450OO03		30 m									
		L0450OO04		40 m									
		L0450OO05		50 m									
		L0450OO06		60 m									
		L0450OO07		70 m									
		L0450OO08		80 m									
		L0450OO10		100 m									
		L0451OO10	red	100 m spool									
		L0451OO20		200 m spool									
		L0450RR03		30 m									
		L0450RR04		40 m									
		L0450RR05		50 m									
		L0450RR06		60 m									
		L0450RR07		70 m									
		L0450RR08		80 m									
		L0450RR10	white	100 m									
		L0451RR10		100 m spool									
		L0451RR20		200 m spool									
		L0450WG03		30 m									
		L0450WG04		40 m									
		L0450WG05		50 m									
		L0450WG06		60 m									
		L0450WG07		70 m									
L0450WG08	white	80 m											
L0450WG10		100 m											
L0451WG10		100 m spool											
L0451WG20		200 m spool											





LOW STRETCH ROPES		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC R44 10.5    	Low stretch rope type A designed for general use with patented rope-braiding technology ROUTE 44.	L0430BB03	black	30 m	10.5	72	3.4	315	19.8	15	A	EN 1891 	CE 1019
		L0430BB04		40 m									
		L0430BB05		50 m									
		L0430BB06		60 m									
		L0430BB07		70 m									
		L0430BB08		80 m									
		L0430BB10		100 m									
		L0431BB10		100 m spool									
		L0431BB20		200 m spool									
		L0430KK03		khaki									
		L0430KK04	40 m										
		L0430KK05	50 m										
		L0430KK06	60 m										
		L0430KK07	70 m										
		L0430KK08	80 m										
		L0430KK10	100 m										
		L0431KK10	100 m spool										
		L0431KK20	200 m spool										
		L0430RR03	red										
		L0430RR04		40 m									
		L0430RR05		50 m									
		L0430RR06		60 m									
		L0430RR07		70 m									
		L0430RR08		80 m									
		L0430RR10		100 m									
		L0431RR10		100 m spool									
		L0431RR20		200 m spool									
		L0430WR03		white									
		L0430WR04	40 m										
		L0430WR05	50 m										
		L0430WR06	60 m										
		L0430WR07	70 m										
L0430WR08	80 m												
L0430WR10	100 m												
L0431WR10	100 m spool												
L0431WR20	200 m spool												





LOW STRETCH ROPES		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC 11.0   	STATIC rope for workers at height, rescuers, firemen, cavers and other professionals when working every day.	L0250BB03	black	30 m	11	80	3.3	34.5	22	20	A	EN 1891 	CE 1019
		L0250BB04		40 m									
		L0250BB05		50 m									
		L0250BB06		60 m									
		L0250BB07		70 m									
		L0250BB08		80 m									
		L0250BB10		100 m									
		L0251BB10		100 m spool									
		L0251BB20		200 m spool									
		L0250RR03		red									
		L0250RR04	40 m										
		L0250RR05	50 m										
		L0250RR06	60 m										
		L0250RR07	70 m										
		L0250RR08	80 m										
		L0250RR10	100 m										
		L0251RR10	100 m spool										
		L0251RR20	200 m spool										
		L0250WR03	white										
		L0250WR04		40 m									
		L0250WR05		50 m									
		L0250WR06		60 m									
		L0250WR07		70 m									
		L0250WR08		80 m									
L0250WR10	100 m												
L0251WR10	100 m spool												
L0251WR20	200 m spool												



LOW STRETCH ROPES		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC 10.5 	Low stretch rope type A intended for rope access, work positioning, rescue, caving or manipulation with the objects.	L0230BB03	black	30 m	10.5	69	3.3	30.4	18.6	10	A	EN 1891 A	CE 1019
		L0230BB04		40 m									
		L0230BB05		50 m									
		L0230BB06		60 m									
		L0230BB07		70 m									
		L0230BB08		80 m									
		L0230BB10		100 m									
		L0231BB10		100 m spool									
		L0231BB20	200 m spool										
		L0230KK03	khaki	30 m									
		L0230KK04		40 m									
		L0230KK05		50 m									
		L0230KK06		60 m									
		L0230KK07		70 m									
		L0230KK08		80 m									
		L0230KK10		100 m									
		L0231KK10		100 m spool									
		L0231KK20	200 m spool										
		L0230RR03	red	30 m									
		L0230RR04		40 m									
		L0230RR05		50 m									
		L0230RR06		60 m									
		L0230RR07		70 m									
		L0230RR08		80 m									
		L0230RR10		100 m									
		L0231RR10		100 m spool									
		L0231RR20	200 m spool										
		L0230WR03	white	30 m									
L0230WR04	40 m												
L0230WR05	50 m												
L0230WR06	60 m												
L0230WR07	70 m												
L0230WR08	80 m												
L0230WR10	100 m												
L0231WR10	100 m spool												
L0231WR20	200 m spool												
CONTRA 11 	Static rope with polyamide core and polyester sheath. Polyester sheath reduces elongation, has greater resistance to moisture and abrasion.	L0270WX03		30 m	11	84	3.3	32	18	10	A	EN 1891 A	CE 1019
		L0270WX04		40 m									
		L0270WX05		50 m									
		L0270WX06		60 m									
		L0270WX07		70 m									
		L0270WX08		80 m									
		L0270WX10		100 m									
		L0271WX10		100 m - spool									
		L0270WX20		200 m - spool									
		CONTRA 10.5 		All-purpose STATIC rope providing a balance between flexibility and abrasion resistance.									
L0260WX04	40 m												
L0260WX05	50 m												
L0260WX06	60 m												
L0260WX07	70 m												
L0260WX08	80 m												
L0260WX10	100 m												
L0261WX10	100 m spool												
L0261WX20	200 m spool												













LOW STRETCH ROPES		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELONGATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC 9.0  	STATIC rope type B. Low stretch rope of a lower performance than type A ropes, requiring greater care in use.	L0220BB03	black	30 m	9	54	4	24.4	13.3	15	B	EN 1891 	CE1019
		L0220BB04		40 m									
		L0220BB05		50 m									
		L0220BB06		60 m									
		L0220BB07		70 m									
		L0220BB08		80 m									
		L0220BB10		100 m									
		L0221BB10		100 m spool									
		L0221BB20		200 m spool									
		L0220WR03		30 m									
		L0220WR04	40 m										
		L0220WR05	50 m										
		L0220WR06	60 m										
		L0220WR07	70 m										
		L0220WR08	80 m										
		L0220WR10	100 m										
		L0221WR10	100 m spool										
		L0221WR20	200 m spool										



LOW STRETCH ROPES NFPA		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELONGATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC R44 NFPA 13 	Durable STATIC rope designed for general use for rope access and rescue. The rope meets the most demanding requirements of the North American NFPA standard, which demands the highest quality in everyday use.	R0460WB04	white	46 m/150 ft	13	108.7	3.4 % (at 1.35 kN, 300 lbs)	47	30		A	NFPA 1983 "G"	x
		R0460WB06		61 m/200 ft									
		R0460WB09		92 m/300 ft									
		R0461WB10		100 m/330 ft - spool									
		R0461WB18		183 m/600 ft - spool									
		R0461WB20		200 m/660 fr - spool									

STATIC R44 NFPA 11    	Durable STATIC rope designed for technical use for rope access and rescue. The rope meets the most demanding requirements of the North American NFPA standard, which demands the highest quality in everyday use.	R0450BB04	black	46 m/150 ft	11	77	3.0 % (at 1.35 kN, 300 lbs); 6.8 % (at 2.7 kN, 600 lbs); 10.8 % (at 4.4 kN, 1000 lbs)	33.5	x	x	A	NFPA 1983 „T“ EN 1891 	CE1019
		R0450BB06		61 m/200 ft									
		R0450BB09		92 m/300 ft									
		R0451BB10		100 m/330 ft - spool									
		R0451BB18		183 m/600 ft - spool									
		R0451BB20		200 m/660 fr - spool									
		R0450OO04	46 m/150 ft										
		R0450OO06	61 m/200 ft										
		R0450OO09	92 m/300 ft										
		R0451OO10	100 m/330 ft - spool										
		R0451OO18	183 m/600 ft - spool										
		R0451OO20	200 m/660 fr - spool										
		R0450RR04	46 m/150 ft										
		R0450RR06	61 m/200 ft										
		R0450RR09	92 m/300 ft										
		R0451RR10	100 m/330 ft - spool										
		R0451RR18	183 m/600 ft - spool										
		R0451RR20	200 m/660 fr - spool										
		R0450WG04	46 m/150 ft										
		R0450WG06	61 m/200 ft										
R0450WG09	92 m/300 ft												
R0451WG10	100 m/330 ft - spool												
R0451WG18	183 m/600 ft - spool												
R0451WG20	200 m/660 fr - spool												

LOW STRETCH ROPES NFPA		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
STATIC R44 NFPA 10.5    	Durable STATIC rope designed for technical use for rope access and rescue. The rope meets the most demanding requirements of the North American NFPA standard, which demands the highest quality in everyday use.	R0430BB04	black	46 m/150 ft	10.5	72	3.5 % (at 1.35 kN, 300 lbs); 7.2 % (at 2.7 kN, 600 lbs); 9.9 % (at 4.4 kN, 1000 lbs)	32	X	X	A	NFPA 1983 „T” EN 1891 ⚠	CE 1019
		R0430BB06		61 m/200 ft									
		R0430BB09		92 m/300 ft									
		R0431BB10		100 m/330 ft - spool									
		R0431BB18		183 m/600 ft - spool									
		R0431BB20		200 m/660 fr - spool									
		R0430KK04	khaki	46 m/150 ft									
		R0430KK06		61 m/200 ft									
		R0430KK09		92 m/300 ft									
		R0431KK10		100 m/330 ft - spool									
		R0431KK18		183 m/600 ft - spool									
		R0431KK20		200 m/660 fr - spool									
		R0430RR04	red	46 m/150 ft									
		R0430RR06		61 m/200 ft									
		R0430RR09		92 m/300 ft									
		R0431RR10		100 m/330 ft - spool									
		R0431RR18		183 m/600 ft - spool									
		R0431RR20		200 m/660 fr - spool									
		R0430WR04	white	46 m/150 ft									
		R0430WR06		61 m/200 ft									
R0430WR09	92 m/300 ft												
R0431WR10	100 m/330 ft - spool												
R0431WR18	183 m/600 ft - spool												
R0431WR20	200 m/660 fr - spool												

SPELEO ROPES		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STATIC ELON- GATION %	STRENGTH kN	KNOT BREAKING FORCE kN	NUMBER OF FALLS	TYPE	STANDARD	CE
SPELEO R44 10.5 	STATIC rope with patented rope-braiding technology ROUTE 44 developed especially for cave exploring.	L0440WR03	white	30 m	10.5	72	3.3	33.4	18.8	9	A	EN 1891 ⚠	CE 1019
		L0440WR04		40 m									
		L0440WR05		50 m									
		L0440WR06		60 m									
		L0440WR07		70 m									
		L0440WR08		80 m									
		L0440WR10		100 m									
		L0441WR10		100 m - spool									
		L0441WR20		200 m - spool									
SPELEO 10.5 	Speleological rope designed for smooth rappelling of long lengths. The rope behaves the same in wet and dirty conditions.	L0240WR03	white	30 m	10.5	70	4	29.4	17.2	10	A	EN 1891 ⚠	CE 1019
		L0240WR04		40 m									
		L0240WR05		50 m									
		L0240WR06		60 m									
		L0240WR07		70 m									
		L0240WR08		80 m									
		L0240WR10		100 m									
		L0241WR10		100 m - spool									
		L0241WR20		200 m - spool									

ACCESSORY CORDS		CODE	COLOR	LENGTH	DIAMETER mm	WEIGHT g/m	STRENGTH kN	STANDARD	CE	
HAMMER CORD 2 mm		Accessory cord for securing climbing or working gear	L0021XX00	grey	metrage	2	2.8	1.2	✘	✘
HAMMER CORD 3 mm		Accessory cord for securing climbing or working gear	L0031XX00	yellow	metrage	3	6.5	1.9	✘	✘
Accessory cords 4 mm		Accessory cords for all vertical adventures. Rescue and self-protection.	L0041AG10	blue	100 m spool	4	12.6	3.2	EN 564 	CE1019
Accessory cords 5 mm		Accessory cords for all vertical adventures. Rescue and self-protection.	L0051OG10	orange	100 m spool	5	18.7	5	EN 564 	CE1019
			L0051BB10	black	100 m spool					
Accessory cords 6 mm		Accessory cords for all vertical adventures. Rescue and self-protection.	L0061BB10	black	100 m spool	6	23.2	9	EN 564 	CE1019
			L0061YG10	yellow	100 m spool					
Accessory cords 7 mm		Accessory cords for all vertical adventures. Rescue and self-protection.	L0071RG10	red	100 m spool	7	35.1	11.5	EN 564 	CE1019
Accessory cords 8 mm		Accessory cords for all vertical adventures. Rescue and self-protection.	L0081PG10	blue	100 m spool	8	39.8	14.6	EN 564 	CE1019

ROPE ACCESSORIES		CODE	COLOR	MATERIAL	Length cm/in	WEIGHT g/lb	
DEFENDER		Has capacity for two or more ropes. Protects rope sheath against abrasion on rough surfaces and edges. Has capacity for two or more ropes.	W1027B080	black	Cortex	80 32	✘
			W1027B120			120 47	
ROPE PROTECTOR		Protects rope sheath against abrasion on rough surfaces and edges.	W8100B050	various	PVC	50 20	✘
			W8100B070			70 28	
			W8100B100			100 39	
			W8100B120			120 47	
EDGE ROLLER		Compact light edge roller for rope protection. Protects a moving rope against the abrasion. Basic set consists of 3 modules and 4 maillons.	K0050OS03	orange + silver	aluminium alloy	✘	777 27.41
			K0050OS01			232 8.18	
EDGE ROLLER PRO		Rope protector with movable rollers for minimal rope friction.	RK812OS00	orange + silver	Side plates – light alloy, axle and bearings – steel	✘	550 19.40
ATIKA		Very stable rope protector with rubber layer on the lower side eliminates unwanted movement. Ensures safe work at height and load lifting over sharp edges.	RK900PP00	silver	stainless steel + rubber	✘	1450 51
THERMOCUTTER		Electric thermo-cutter is ideal machine for cutting the ropes and accessory cords.	X0004GB00	green	✘	✘	✘
ROPEMARKER		Marker for climbing and working equipment.	X0015XX00	black	✘	✘	✘